Datasheet

LuxaLight Industrial LED Fixture Polarised cover Neutral White 4200K 24.2x16mm (24 Volt, 2835, IP64)

LF-24-4200-24.2X16-POL

Version: 2025-03-28.1

Email: info@luxalight.eu

Website: www.luxalight.eu Tel.: +31 (0)40 - 202 49 04

Product description

The **LuxaLight Industrial LED Fixture (4200K)** is a high-quality fixture designed for applications that require high light output, precision, and excellent color rendering. The fixture is made from durable aluminum, ensuring robust and reliable construction, while also providing optimized *heat management* to prevent overheating and maximize system efficiency.

Key Features:

- 4200K Color Temperature: The neutral white light at 4200K provides a balanced spectrum, with a strong focus on 650 nm and 675 nm wavelengths for red light, essential for photosynthesis and plant growth. The LED fixture also has a high peak at 450 nm, ideal for promoting chlorophyll production and other biological processes.
- High PAR Flux (2726
 µmol/m²/s at 5 cm): The LED fixture delivers high light intensity in the form of PAR, ideal for promoting
 photosynthesis and plant growth. This makes it an excellent choice for horticulture and other applications requiring intense light.
- Aluminum Fixture for Optimal Heat Management: The fixture is made from high-quality aluminum, ensuring efficient heat
 dissipation and optimizing the performance of the LED fixture. This prevents overheating, ensuring the product operates at its best
 at all times.
- Polarized Cover for Different Light Distribution Variants: The polarized cover is available in different variants, including 0°, 60°, 90°, and 120°, allowing for customized light spread based on the specific needs of the application. This makes the fixture suitable for a wide range of applications, from large growing spaces to smaller research environments.
- Compatibility with Pollux for Pulse Mode: The LuxaLight LED Fixture can be used in combination with the Pollux, which
 provides the ability to adjust light intensity in pulses. This allows the light cycle to be tailored to specific needs, optimizing
 photosynthesis and plant growth.
- Easy Integration: The LED fixture is designed for easy integration into existing systems or enclosures, providing flexibility for a wide range of horticultural and light-related applications.
- Real-Time Temperature Monitoring via NTC Sensor: The integrated NTC sensor continuously measures and adjusts
 temperature, maintaining optimal operating conditions. This prevents overheating and ensures the LED fixture always performs at
 its best, maximizing output for consistent and long-lasting results.

Applications:

- Horticulture and Plant Lighting: The 4200K color temperature and high PAR flux make this LED fixture ideal for horticultural
 applications, where a broad spectrum of light is necessary to promote photosynthesis, with a strong focus on 650 nm and 675 nm
 for red light and a peak at 450 nm for blue light. The polarized cover with different light distribution variants offers flexibility for
 various growing environments.
- Plant Research and Growth Optimization: With its balanced light spectrum, including specific wavelengths of 650 nm, 675 nm, and 450 nm, the LED fixture is ideal for scientific research on plant growth, photosynthesis, and other biological processes influenced by light intensity and quality.
- Growing Facilities and Vertical Farming: The LED fixture provides powerful lighting for controlled growing environments in greenhouses, vertical farming, and other indoor growing applications, where specific light spectrums and high PAR flux are essential for maximum yield and plant health. The polarized cover offers various light distribution options that can be customized to the needs of the growing environment.
- Plant and Product Quality Control: The LED fixture is also suitable for quality control of plants, crops, or other biological
 products in agriculture and horticulture, providing consistent lighting that accurately simulates growth conditions.

Benefits:

- Full Spectrum with High Peaks at 450 nm and Red Light (650 nm & 675 nm): The extensive light spectrum, with specific wavelengths for blue light (450 nm) and red light (650 nm & 675 nm), offers powerful lighting for photosynthesis and plant growth.
- High PAR Flux: The high PAR flux of 2726 µmol/m²/s at 5 cm ensures sufficient light intensity, essential for promoting healthy plant growth, especially in commercial growing environments.

KvK-nummer: 57580561

BTW-nummer: NL852642209B01

IBAN: NL87 INGB 0007 8159 75

BIC/SWIFT code: INGBNL2A

- Flexibility in Light Distribution: The polarized cover is available in different variants, including 0°, 60°, 90°, and 120°, allowing for customized light spread based on the specific needs of the application.
- Efficient Performance: The LED fixture provides reliable and efficient performance with consistent light output, making it ideal for intensive growth applications such as horticulture, where long-lasting and dependable lighting is required.

Email: info@luxalight.eu

Website: www.luxalight.eu

Tel.: +31 (0)40 - 202 49 04

Technical specifications

General					
Brand	LuxaLight				
Application	Food Inspection (Agro-Food Hyper - spectral Imaging Line Scan Cameras Machine Vision	Food Inspection (Agro-Food) Hyper - spectral Imaging Line Scan Cameras			
LED type	2835				
Material	Aluminum				
Dimensions	220 × 24,2 × 16 mm				
Mounting	Surface mounted				
Cover type	PMMA Polarised transparen	nt			
_EDs per piece	108.00				
Lighting					
Color temperature	4200 K				
Measurement results					
PPFD		Value Measuring di			
		Value			
		1811 µmol/m2			
	574 μmol/m2	908 µmol/m2			
	179 µmol/m2				
	88 µmol/m2		200 mm 300 mm		
	54 μmol/m2				
	36 μmol/m2				
rradiance	Volue	Value Me			
	408 W/m2				
	205 W/m2	50 75			
	129 W/m2		mm		
	40 W/m2				
	20 W/m2				
	12 W/m2	400	400 mm		
	8 W/m2	600	mm		
Illuminance	Value	Measu	ring distance		
	118 klux	50 mm			
	60 klux	75 mm			
	38 klux	100 mm	1		
	12 klux				
	6 klux	300 mm			
	3,5 klux	400 mm			
	2,3 klux	2,3 klux 600 mm			

Email: info@luxalight.eu

Website: www.luxalight.eu

Tel.: +31 (0)40 - 202 49 04

	 By combining Pulse Mode with Real-Time Monitoring, the efficiency of LED systems can be increased, resulting in higher output. We have the expertise and equipment to perform measurements tailored to the specific requirements of the application. 		
Electronics			
Working voltage	24V		
Current per piece	1.25 A / piece		
Power consumption per piece	30.00 W / piece		
PCB material	Aluminium		
Pinout	Symbol	Function	
	V+	V+	
	GND	Ground	
	NTC	NTC sensor	
	NTC_GND	NTC ground	
NTC parameters	Resistance: 5000 Ohm Beta value: 3950		
Environmental			
Operating temperature	-20 ~ +60 °C		
Storage temperature	-40 ~ +80 °C		
IP class	IP 64		
Directives - standards - certificates			
Directives	RoHS CE		
Safety standards	EN60598-1 EN62031 IEC62471		

While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, LuxaLight does not guarantee that it is error - free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalogue are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.

Email: info@luxalight.eu

Website: www.luxalight.eu

Tel.: +31 (0)40 - 202 49 04