

Datasheet

LuxaLight Industrial LED Fixture Opaline Cover RGBW 24.2x16mm (24 Volt, 5050, IP64)

LF-24-RGBW-24.2X16-OC

Version: 2025-08-02.2

Technical specifications

General	
Brand	LuxaLight
Application	Horticulture
LED type	5050
Material	Aluminum
Dimensions	220 × 24,2 × 16 mm
Mounting	Surface mounted
Warranty	5 years
Cover type	PMMA opal
LEDs per piece	36.00

Lighting	
Color temperature	2650 K
CRI	≥ 95
Wave length Red	620~630 nm
Wave length Green	510 ~ 520 nm
Wave length Blue	450 ~ 460 nm
BIN	3 SDCM
Beam angle	120 °
LB waarde	L80B50

Measurement results	
Illuminance (Lux) (Object size: 1 piece)	24V
	5cm 34510 lx
	10cm 14080 lx
	15cm 7229 lx
	20cm 4486 lx
	25cm 3023 lx
	30cm 2280 lx
Total PPFD umol/m2 (PAR 400-700nm) (Object size: 1 piece)	24V
	5cm 601.212 umol/m2
	10cm 244.775 umol/m2
	15cm 125.704 umol/m2
	20cm 78.0229 umol/m2
	25cm 52.5608 umol/m2
	30cm 39.6553 umol/m2

- By combining Pulse Mode with Real-Time Monitoring, the efficiency of LED systems can be increased, resulting in higher output.
- We have the expertise and equipment to perform measurements tailored to the specific requirements of the application.

Electronics	
Working voltage	24V

Current per piece	0.40 A / piece													
Power consumption per piece	9.60 W / piece													
PCB material	Aluminium													
Pinout	<table><tr><th>Symbol</th><th>Function</th></tr><tr><td>V+</td><td>V+</td></tr><tr><td>R</td><td>Red channel</td></tr><tr><td>G</td><td>Green channel</td></tr><tr><td>B</td><td>Blue channel</td></tr><tr><td>W</td><td>White channel</td></tr></table>		Symbol	Function	V+	V+	R	Red channel	G	Green channel	B	Blue channel	W	White channel
	Symbol	Function												
	V+	V+												
	R	Red channel												
	G	Green channel												
	B	Blue channel												
W	White channel													

Environmental


Operating temperature	-20 ~ +60 °C
Storage temperature	-40 ~ +80 °C
IP class	IP 64

Directives - standards - certificates


Directives	RoHS CE
Safety standards	EN60598-1 EN62031 IEC62471

Measurement results

irradiance - full-spectrum (24V)



cie1931



While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, LuxaLight does not guarantee that it is error - free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalogue are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.