

Datasheet

LuxaLight Industrial LED Fixture Transparent IP68 RGBW 24.2x16mm (24 Volt, 5050, IP68)

LF-24-RGBW-24.2X16-PU

Version: 2025-08-02.1

Technical specifications

General	
Brand	LuxaLight
Application	Horticulture
LED type	5050
Material	Aluminum
Dimensions	220 × 24,2 × 16 mm
Mounting	Surface mounted
Cover type	Polyurethane
LEDs per piece	36.00

Lighting	
Color temperature	2650 K
CRI	≥ 95
Wave length Red	620 ~ 630 nm
Wave length Green	510 ~ 520 nm
Wave length Blue	450 ~ 460 nm
BIN	3 SDCM
Beam angle	120 °
LB waarde	L80B50

Measurement results

Illuminance (Lux) (Object size: 1 piece)	24V	
	5cm	40230 lx
	10cm	12830 lx
	15cm	6330 lx
	20cm	3831 lx
	25cm	2535 lx
	30cm	1893 lx

Total PPFD umol/m2 (PAR 400-700nm) (Object size: 1 piece)	24V	
	5cm	711.955 umol/m2
	10cm	226.587 umol/m2
	15cm	111.481 umol/m2
	20cm	67.358 umol/m2
	25cm	44.6637 umol/m2
	30cm	33.3736 umol/m2

- By combining Pulse Mode with Real-Time Monitoring, the efficiency of LED systems can be increased, resulting in higher output.
- We have the expertise and equipment to perform measurements tailored to the specific requirements of the application.

Electronics	
Working voltage	24V
Current per piece	0.40 A / piece

Power consumption per piece 9.60 W / piece

PCB material Aluminium

Pinout

Symbol	Function
V+	V+
R	Red channel
G	Green channel
B	Blue channel
W	White channel

NTC parameters Resistance: 5000 Ohm
Beta value: 3950

Environmental

Operating temperature -20 ~ +60 °C

Storage temperature -40 ~ +80 °C

IP class IP 68


Directives - standards - certificates

Directives RoHS
CE


Safety standards EN60598-1
EN62031
IEC62471

Measurement results

irradiance - full-spectrum (24V)



cie1931



While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, LuxaLight does not guarantee that it is error - free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalogue are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.