

Datasheet

LuxaLight Industrial LED Fixture Transparent Cover RGBW 24.2x16mm (24 Volt, 5050, IP64)

LF-24-RGBW-24.2X16-TC

Version: 2025-08-02.2

Technical specifications

General

Brand	LuxaLight
Application	Horticulture Hyper - spectral Imaging
LED type	5050
Material	Aluminum
Dimensions	220 × 24,2 × 16 mm
Mounting	Surface mounted
Warranty	5 years
Cover type	PMMA transparent
LEDs per piece	36.00

Lighting

Color temperature	2650 K
CRI	≥ 95
Wave length Red	620~630 nm
Wave length Green	510 ~ 520 nm
Wave length Blue	450 ~ 460 nm
BIN	3 SDCM
Beam angle	120 °
LB waarde	L80B50

Measurement results

Illuminance (Lux)
(Object size: 1 piece)

	24V
5cm	34510 lx
10cm	14080 lx
15cm	7229 lx
20cm	4486 lx
25cm	3023 lx
30cm	2280 lx

Total PPFD umol/m2 (PAR 400-700nm)
(Object size: 1 piece)

	24V
5cm	601.212 umol/m2
10cm	244.775 umol/m2
15cm	125.704 umol/m2
20cm	78.0229 umol/m2
25cm	52.5608 umol/m2
30cm	39.6553 umol/m2


- By combining Pulse Mode with Real-Time Monitoring, the efficiency of LED systems can be increased, resulting in higher output.
- We have the expertise and equipment to perform measurements tailored to the specific requirements of the application.

Electronics


Working voltage	24V												
Current per piece	0.40 A / piece												
Power consumption per piece	9.60 W / piece												
PCB material	Aluminium												
Pinout	<table> <tr> <th>Symbol</th><th>Function</th></tr> <tr> <td>V+</td><td>V+</td></tr> <tr> <td>R</td><td>Red channel</td></tr> <tr> <td>G</td><td>Green channel</td></tr> <tr> <td>B</td><td>Blue channel</td></tr> <tr> <td>W</td><td>White channel</td></tr> </table>	Symbol	Function	V+	V+	R	Red channel	G	Green channel	B	Blue channel	W	White channel
Symbol	Function												
V+	V+												
R	Red channel												
G	Green channel												
B	Blue channel												
W	White channel												
NTC parameters	Resistance: 5000 Ohm Beta value: 3950												
Environmental													
Operating temperature	-20 ~ +60 °C												
Storage temperature	-40 ~ +80 °C												
IP class	IP 64												
Directives - standards - certificates													
Directives	RoHS CE												
Safety standards	EN60598-1 EN62031 IEC62471												

Measurement results

irradiance - full-spectrum (24V)



cie1931



While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, LuxaLight does not guarantee that it is error - free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalogue are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.