

## Datasheet

LED Strip Specification

LED strip type:  
**LS12WW60X3528PLX**

Description:  
**LuxaLight LED Strip 12V Warm White Protected 3528**  
**(12 Volt, 60 LEDs, 3528, IP64)**



Date:  
11-7-2015

Page 1 of 4

## Parameters:

| Basic Parameters  |                   |
|-------------------|-------------------|
| LED Type          | 3528 SMD          |
| Color             | Warm White        |
| CRI               | ≥ 80 Ra           |
| Viewing Angle (θ) | 120 ±5°           |
| LED Qty           | 60 LEDs / mtr     |
| IP grade          | IP64 Silicone     |
| Dimensions        | 1000 * 8 * 4mm    |
| Weight            | 40g ~ 50g / meter |
| Lifespan          | 50,000hours       |
| LB Value          | L80B50            |

| Environment Parameters |               |
|------------------------|---------------|
| Working Temperature    | -25°C ~ +70°C |
| Storage Temperature    | -20°C ~ +60°C |


| Electronic Specifications |                  |
|---------------------------|------------------|
| Working Voltage           | DC12V            |
| Working Current           | 0.4A / mtr       |
| Working Wattage           | 4.8W / mtr       |
| Driving Method            | Constant Voltage |

| Wires & connection length |                  |
|---------------------------|------------------|
| Wires                     | UL1007 20# 150mm |
| Length per segment        | 50mm             |
| LEDs / segment            | 3                |
| Standard length on a reel | 10m              |


| Luminous Flux (Lumen/Meter) |           |
|-----------------------------|-----------|
| Warm White                  | 360 Lumen |
|                             |           |
|                             |           |

| Wave Length/ Color Temperature (nm/k) |               |
|---------------------------------------|---------------|
| Warm White                            | 2500 ~ 2700 K |
|                                       |               |
|                                       |               |


**CIE1931:**



**Optical Characteristics Curve:**



**Wave Length:**



## **The Materials of PCB:**

Epoxy PCB with white finishing.  
Conducting Tracks: Cu, 35um thickness, double sided.

Solderings:  
Solder Alloy: 99.3 Sn, 0.7 Cu,  
Melting Temperature: 227°C  
No SVHC (17-Dec-2014)

## **Certificate of Conformity:**

EC Council Directive 2004/108/EC  
Electromagnetic Compatibility  
Registration No.: ATE20120944

Complies to the Standards:

- EN 55015: 2006 + A1: 2007 + A2: 2009
- EN 61000-3-2: 2006 + A1: 2009 + A2: 2009
- EN 61000-3-3: 2008
- EN 61547: 2009

While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.