

Datasheet

LED Strip Specification

LED strip type:

LS12RGB96WS2812BVP

Description:

**WS2812B (GS8208) 12V Digital RGB Protected High Power
(12 Volt, 96 LEDs, 5050, IP64)**



Date:
11-7-2015

Page 1 of 5

Parameters:

Basic Parameters	
LED Type	5050 SMD
Color	RGB
Viewing Angle (θ)	120 \pm 5°
LED Qty	96 LEDs / mtr
LEDs per pixel	1
Numbers of channels	3
IC type	WS2812 (GS8208)
IP grade	IP64 Silicone
Dimensions	1000 * 12 * 4mm
Weight	35g ~ 40g / meter
Lifespan	70,000hours
LB Value	L80B50
Warranty	2 Years

Environment Parameters	
Working Temperature	-25°C ~ +70°C
Storage Temperature	-20°C ~ +60°C


Electronic Specifications	
Working Voltage	DC 12V
Working Current	1.6 A / mtr
Working Wattage	19.2 W / mtr
Driving Method	Constant Voltage

Wires & connection length	
Wires	UL1007 20# 150mm
Length per segment	16.67 mm
LEDs / segment	1
Standard length on a reel	10m


Luminous Flux (Lumen/Meter)	
Red	200 Lumen
Green	290 Lumen
Blue	185 Lumen

Wave Length/ Color Temperature	(nm/k)
Red	620~630 nm
Green	510~525 nm
Blue	455~470 nm


CIE1931 RED:



CIE1931 Green:




CIE1931 Blue:




Wave Length Red:

mW/m²/nm




Wave Length Green:

mW/m²/nm



Wave Length Blue:

mW/m²/nm



The Materials of PCB:

Epoxy PCB with white finishing.
Conducting Tracks: Cu, 35um thickness, double sided.

Solderings:
Solder Alloy: 99.3 Sn, 0.7 Cu,
Melting Temperature: 227°C
No SVHC (17-Dec-2014)

Certificate of Conformity:

EC Council Directive 2004/108/EC
Electromagnetic Compatibility

Complies to the Standards:

- EN 55015: 2006 + A1: 2007 + A2: 2009
- EN 61000-3-2: 2006 + A1: 2009 + A2: 2009
- EN 61000-3-3: 2008
- EN 61547: 2009

While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.