

Datasheet

LED Strip Specification

LED strip type:
LS30R120X3528PLX

Description:
LuxaLight Long Life LED Strip 30V Red Protected 3528
(30 Volt, 120 LEDs, 3528, IP64)



Date:
11-7-2015

Page 1 of 4

Parameters:

Basic Parameters	
LED Type	3528 SMD
Color	Red
Viewing Angle (θ)	120 ±5°
LED Qty	120 LEDs / mtr
IP grade	IP64
Dimensions Reel	1000 * 8 * 3mm
Weight	30g ~ 35g / meter
Lifespan	50,000hours
LB Value	L80B50
Warranty	5 Years

Environment Parameters	
Working Temperature	-25°C ~ +70°C
Storage Temperature	-20°C ~ +60°C


Electronic Specifications	
Working Voltage	DC30V
Working Current	0.4A / mtr
Working Wattage	12W / mtr
Driving Method	Constant Voltage

Wires & connection length	
Wires	UL1007 20# 150mm
Length per segment	100mm
LEDs / segment	12
Standard length on a reel	10m


Luminous Flux (Lumen/Meter)	
Red	300 Lumen

Wave Length/ Color Temperature	(nm/k)
Red	620~630 nm


CIE1931:



Optical Characteristics Curve:



Wave Length:



The Materials of PCB:

Epoxy PCB with white finishing.
Conducting Tracks: Cu, 35um thickness, double sided.

Solderings:
Solder Alloy: 99.3 Sn, 0.7 Cu,
Melting Temperature: 227°C
No SVHC (17-Dec-2014)

Certificate of Conformity:

EC Council Directive 2004/108/EC
Electromagnetic Compatibility

Complies to the Standards:

- EN 55015: 2006 + A1: 2007 + A2: 2009
- EN 61000-3-2: 2006 + A1: 2009 + A2: 2009
- EN 61000-3-3: 2008
- EN 61547: 2009

While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.