

Datasheet

LED Strip Specification

LED strip type:
LP12V3LTM1914

Description:
Digitale LED Pixel 12V 3-LED TM1914 32mm



Date:
11-7-2015

Page 1 of 3

Parameters:

Basic Parameters	
LED Type	5050 SMD
Color	RGB
Viewing Angle (θ)	180 ±5°
LEDs per pixel	3
Numbers of channels	3
IC type	TM1914
IP grade	IP64
Dimensions	32mm x 20mm
Weight	2 Gram
Lifespan	50,000hours
LB Value	L80B50
Warranty	2 Years

Environment Parameters	
Working Temperature	-25°C ~ +70°C
Storage Temperature	-20°C ~ +60°C

Electronic Specifications	
Working Voltage	DC 12V
Working Current	0.06 A / mtr
Working Wattage	0.75 W / mtr
Driving Method	Constant Voltage

Dimensions	
Wires	80 mm
Pixel diameter	35 mm
Total height	26 mm
Thread	27 mm
Hole diameter	27 mm
Nut diameter	38 mm
Installation	20 mm

Luminous Flux (Lumen/Meter)	
50 Lumen	

Wave Length/ Color Temperature	(nm/k)
Red	620 ~ 630 nm
Green	510 ~ 525 nm
Blue	455 ~ 470 nm

Wire color	Symbol	Function description
White	GND	Ground
Blue	D2	Data 2
Green	D1	Data 1
Red	+12V	12V logic power supply

Certificate of Conformity:

EC Council Directive 2004/108/EC
Electromagnetic Compatibility

Complies to the Standards:

- EN 55015: 2006 + A1: 2007 + A2: 2009
- EN 61000-3-2: 2006 + A1: 2009 + A2: 2009
- EN 61000-3-3: 2008
- EN 61547: 2009

While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.