

Datasheet

LED Strip Specification

LED strip type:

LS24RGBW72TM1814PLX

Description:

**TM1814 Digital RGBW High Power Protected
(24 Volt, 72 LEDs, 5050, IP64)**



Date:
11-7-2015

Page 1 of 5

Parameters:

Basic Parameters	
LED Type	5050 SMD
Color	RGBW
Viewing Angle (θ)	120 ±5°
CRI	≥ 80
LED Qty	72 LEDs / mtr
LEDs per pixel	6
Numbers of channels	4
IC type	TM1814
IP grade	IP64 Silicone
Dimensions	1000 * 10 * 4mm
Weight	35g ~ 40g / meter
Lifespan	50,000hours
LB Value	L80B50
Warranty	2 Years

Environment Parameters		Electronic Specifications	
Working Temperature	-25°C ~ +70°C	Working Voltage	DC 24V
Storage Temperature	-20°C ~ +60°C	Working Current	0.8 A / mtr
		Working Wattage	19.2 W / mtr
		Driving Method	Constant Voltage


Wires & connection length	
Wires	UL1007 20# 150mm
Length per segment	83.33 mm
LEDs / segment	6
Standard length on a reel	10m

Luminous Flux (Lumen/Meter)	
Red	200 Lumen
Green	290 Lumen
Blue	185 Lumen
Warm White	585 Lumen


Wave Length/ Color Temperature	(nm/k)
Red	620~630 nm
Green	510~525 nm
Blue	455~470 nm
Warm White	2700 K

Wire color	Symbol	Function description
White	GND	Ground
Green	Di	Data IN
Red	+24V	24V logic power supply


CIE1931 Red:




CIE1931 Green:



CIE1931 Blue:




CIE1931 Warm White:




Wavelength Red:

mW/m²/nm




Wavelength Green:

mW/m²/nm




Wavelength Blue:

mW/m²/nm



Wavelength Warm White:

mW/m²/nm



The Materials of PCB:

Epoxy PCB with white finishing.
Conducting Tracks: Cu, 35um thickness, double sided.

Solderings:
Solder Alloy: 99.3 Sn, 0.7 Cu,
Melting Temperature: 227°C
No SVHC (17-Dec-2014)

Certificate of Conformity:

EC Council Directive 2004/108/EC
Electromagnetic Compatibility

Complies to the Standards:

- EN 55015: 2006 + A1: 2007 + A2: 2009
- EN 61000-3-2: 2006 + A1: 2009 + A2: 2009
- EN 61000-3-3: 2008
- EN 61547: 2009

While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.