

Datasheet

LED-strip specification

LED-strip type:
NF24NW120X2835XFLAT

Description:
**LuxaLight Long Life LED Neon Flex Flat View Neutral White 4000K
(24 Volt, 120 LEDs, 2835, IP67)**



Date: 21-07-2021

Page 1 of 4

Basic Parameters	
LED Type	2835 SMD
Color	Neutral White
CRI	≥ 80 Ra
Viewing Angle (θ)	120 ±5°
LED Qty	120 LEDs/ mtr
IP grade	IP67
Dimensions Reel	5000 * 12 * 20mm
Weight	240g ~ 260g/ meter
Lifespan	30,000hours
BIN	3 SDCM
Warranty	2 Years

Environment Parameters	
Working Temperature	-25°C ~ +70°C
Storage Temperature	-20°C ~ +60°C


Electronic Specifications	
Working Voltage	DC24V
Working Current	0.4 A/ mtr
Working Wattage	9.6 W/ mtr
Driving Method	Constant Voltage

Wires & connection length	
Wires	UL1007 20# 150mm
Length per segment	50mm
LEDs / segment	6
Standard length on a reel	5m


Luminous Flux (Lumen/Meter)	
Neutral White	768 Lumen

Wavelength/ Color Temperature	(nm/k)
Neutral White	4000 K


CIE1931 Neutral White:



Optical Characteristics Curve:



Wavelength Neutral White:



The Materials of PCB:

Conducting Tracks: Cu, 35um thickness, double sided.

Solderings:

Solder Alloy: 99.3 Sn, 0.7 Cu,

Melting Temperature: 227°C

No SVHC (Jan 2021)

Certificate of Conformity:

EC Council Directive 2004/108/EC

Electromagnetic Compatibility

Complies to the standards:

- EN 55015: 2019 + A1: 2015 + A2: 2009
- EN 61000-3-2: 2019 + A1: 2009 + A2: 2009
- EN 61000-3-3: 2013
- EN 61547: 2009

While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, LuxaLight does not guarantee that it is error-free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalogue are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.