

Datasheet

LED Science Board specification

LED Science Board type:
LXSCIENCEBOARD1

Description:
**LuxaLight Long Life Aluminium Science Board White, Far Red, Deep Red,
UV-A 365nm Protected
(24 Volt, LEDs, 3535, IP64)**



Date:
09-02-2022

Page 1 of 6

Basic Parameters	
LED Type	2835 SMD
Color	White, Far Red, Deep Red, UV-A
CRI	≥ 90 Ra
Viewing Angle (θ)	120 ±5°
LED Qty	630 LEDs
IP grade	IP64
Dimensions	250* 250 *6mm
Weight	1135g/ per piece
Mounting	Screw / Hang
Lifespan	5000 hours
Warranty	5 Years


Environment Parameters	
Working Temperature	-20°C ~ +50°C
Storage Temperature	-35°C ~ +85°C

Electronic Specifications	
Working Voltage	DC24V
Working Current White	1,88 A/ piece
Working Current Far red	0,43 A/ piece
Working Current Deep red	0,42 A/ piece
Working Current UV-A	0,82 A/ piece
Working Wattage White	45,12 W/ piece
Working Wattage Far red	10,3 W/ piece
Working Wattage Deep red	10,8 W/ piece
Working Wattage UV-A	19,7 W/ piece
Driving Method	Constant Voltage


Wires & connection length	
Wires	Cable 5 × 0,75 mm ² HQ5RR-F
Length	1000mm

Wavelength/ Color Temperature	(nm/k)
White	4100 ~ 4300 K
Far red	650 nm
Deep red	730 nm
UV-A	365 nm


Lighting Angle:




Wavelength white:




Wavelength Far Red:



Wavelength Deep Red:



Wavelength UV-A:



The Materials of PCB:

6mm Thick Aluminium.

Solderings:

Solder Alloy: 99.3 Sn, 0.7 Cu,

Melting Temperature: 227°C

No SVHC (Jan 2021)

Certificate of Conformity:

EC Council Directive 2004/108/EC

Electromagnetic Compatibility

Complies to the standards:

- NEN-EN-IEC 61000-3-2:2019/A1:2021
- NEN-EN-IEC 61000-3-3:2013+A1:2017+A2:2021
- NEN-EN-IEC 61547:2009

While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, LuxaLight does not guarantee that it is error-free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalogue are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.