

# Datasheet

LED-strip specification

LED-strip type:

**LS24BXC0BXPLX**

Description:

**LuxaLight COB LED-strip Blue Protected  
(24 Volt, 512 LEDs, COB, IP64)**



Date:  
14-09-2022

Page 1 of 4

Basic Parameters	
LED Type	COB
Color	Blue
Viewing Angle (θ)	120 ±5°
LED Qty	512 LEDs/ mtr
IP grade	IP64 Silicone
Dimensions	1000 * 10 * 4mm
Weight	35g ~ 50g/ meter
Mounting	3M VHB4905
Lifespan	70,000hours
LB Value	L80B50
BIN	3 SDCM
Warranty	5 Years

Environment Parameters	
Working Temperature	-25°C ~ +75°C
Storage Temperature	-20°C ~ +60°C


Electronic Specifications	
Working Voltage	DC24V
Working Current	0,63 A/ mtr
Working Wattage	15 W/ mtr
Driving Method	Constant Voltage

Wires & connection length	
Wires	UL1007 20# 150mm
Length per segment	50mm
LEDs / segment	24
Standard length on a reel	10m


Luminous Flux (Lumen/Meter)	
Blue	180 Lumen

Wavelength/ Color Temperature (nm/k)	
Blue	455~470 nm


**CIE1931 Blue:**



**Optical Characteristics Curve:**



**Wavelength Blue:**



**The Materials of PCB:**

Conducting Tracks: Cu, 35um thickness, double sided.

**Solderings:**

Solder Alloy: 99.3 Sn, 0.7 Cu,

Melting Temperature: 227°C

No SVHC (Jan 2021)

**Certificate of Conformity:**

EC Council Directive 2004/108/EC

Electromagnetic Compatibility

**Complies to the standards:**

- NEN-EN-IEC 61000-3-2:2019/A1:2021
- NEN-EN-IEC 61000-3-3:2013+A1:2017+A2:2021
- NEN-EN-IEC 61547:2009

While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, LuxaLight does not guarantee that it is error-free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalogue are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.