

Datasheet

LED-strip specification

LED-strip type:
LS30R120X3528ILX

Description:
**LuxaLight LED-strip 30V Red Indoor 3528
(30 Volt, 120 LEDs, 3528, IP20)**




Date:
07-06-2023


Page 1 of 5

Technical Specifications		
LS30R120X3528ILX		
General	LED Type	3528 SMD
	LED Quantity	120 LEDs/m
	Dimensions	10000 * 10 * 3 (L x B x H)
	Segment length	50mm
	LEDs per segment	6 LEDs
	Weight	35 ~ 50g / meter
	Mounting	3M tape VHB4905
Environment	Working Temperature	-20°C ~ +70°C
	Storing Temperature	-20°C ~ +70°C
	IP Grade	IP20
	Mechanical Protection	N.A.
	Lifetime	70.000 Hours
	Warranty	5 Years
Electronic	Working Voltage	DC30V
	Working Current	0,4 A / Engine
	Working Wattage	12W / Engine
	Driving Method	Constant Voltage
Lighting	Engine Wavelength (nm)	630nm Red
	Peak Measured Wavelength (5cm)	632nm
	Luminous Flux / meter	300 Lumen
	LB-value	L80B50
	BIN	3 SDCM
	Viewing Angle (θ)	120 ±5°


Optical Characteristics Curve



Wavelength 630nm:



CIE1931 630nm



The Materials of PCB:

Conducting Tracks: Cu, 35um thickness, double sided.

Solderings:

Solder Alloy: 99.3 Sn, 0.7 Cu,

Melting Temperature: 227°C

No SVHC (Jan 2021)

Certificate of Conformity:

EC Council Directive 2004/108/EC

Electromagnetic Compatibility

Complies to the standards:

- NEN-EN-IEC 61000-3-2:2019/A1:2021
- NEN-EN-IEC 61000-3-3:2013+A1:2017+A2:2021
- NEN-EN-IEC 61547:2009

While LuxaLight has made every reasonable effort to ensure the accuracy of the information in this brochure, LuxaLight does not guarantee that it is error-free, nor does LuxaLight make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. LuxaLight reserves the right to make any adjustments to the information contained herein at any time without notice. LuxaLight expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalogue are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult LuxaLight for the latest dimensions and design specifications.